

TIMBEREX

WOOD FINISHING OIL



TIMBEREX® HARD WAX OIL

Quick drying durable protection for any wood surface

- Very durable, for medium & high traffic areas
- Resistant to liquid spills
- Rapid curing
- High coverage per litre
- Easy application without any special tools

TIMBEREX® HARD WAX OIL

BESKRIVELSE

Timberex Hard Wax Oil is based on a mixture of natural oils and waxes from plants such as Linseed and Soya and harmless odourless solvents. Carnauba wax is used to accelerate the drying of the oil and provide a beautiful finish.

The oils penetrate deeply into the wood surface, protecting it from the inside and keeping it healthy and elastic, whilst the hard wax protects the surface making the wood hardwearing, non slip and easy to maintain. Timberex Hard Wax Oil becomes a permanent part of the wood and requires no sanding when renovating.

Timberex Hard Wax Oil is environmentally friendly, microporous, water repellent, dirt and wear resistant. Will not crack, peel, flake or blister. It is resistant against wine, beer, coffee, tea, fruit juices, and fizzy drinks. EN 71-3 certified (Toy Safe).

ANBEFALT BRUK

This oil is offered in satin and matt finish and can be used on floors, worktops surfaces and furniture. The products is easy-to-apply with no special tools required and will dry within hours and be ready for use within a few hours. TIMBEREX® Hard Wax Oil and can be used for maintenance, repairs and renovation.

TEKNISKE DATA

Tetthet: 0.9
Glansgrad: Matt, Satinert

TØRKETID VED 20°C/50% RELATIV LUFTFUKTIGHET

Overmalbar: 3 h
Herdetid: 7 days

TEORETISK FORBRUK

15 - 20 m² per litre (Priming)
> 50 m² per litre (Maintenance)

KLARGJØRING AV OVERFLATE

Floors should be free from any barrier to penetration. Sand at least twice starting with coarse sandpaper, and use 120 grade maximum sandpaper for the final preparatory sanding. Clean the surface by vacuuming and damp wipe the entire floor and allow to dry.

BRUKSANVISNING

Due to the fast curing nature of this product, application can be completed in one day. We always recommend to test on a small area if possible. Stir the product thoroughly before and during use to ensure consistent dispersion of the carnauba wax.

1. Apply the first coat of TIMBEREX® Hard Wax Oil using a brush, pad or roller. Accidental splashes on surrounding surfaces must be removed at once.
2. Apply a second coat after 3 hours. Apply 2 coats. The oil must not dry between coats.
3. Remove ALL unabsorbed TIMBEREX® Hard-Wax Oil after 15 minutes with cloths, leaving a matt finish at this stage. Place all oil-impregnated cloths etc. into a bucket filled with water. See 'SAFETY' for further information.
4. When the surface has dried overnight, it is important to thoroughly buff with a medium grade nylon pad to close the surface, provide a satin or matt sheen (depending on product) and to remove any minor 'bleed-back'.

PÅFØRINGSBETINGELSER

Timberex Hard Wax Oil should be stored at 20 - 30°C for 8 hours prior to use. Ensure that the oil is stirred prior and during use.

RENGJØRING AV UTSTYR/SPILL

Mild solvent, like white spirit etc.

MERKNADER

CLEANING: Timberex Bio-C Cleaner is recommended for use on all oil treated surfaces. The cleaner is pH-neutral and will not leave any grey film on the surface. Use the right mixture and damp cloth for regular cleaning. Rule of thumb: The surface must be dry within 5-10 minutes or too much water has been used.

MAINTENANCE: Use Timberex Hard Wax Oil for rejuvenating the surface on a regular basis (once a year or when needed). This will also gradually build more resistance to wear and tear, eliminating the need for re-sanding and re-application.

CURING: The surface will normally be sufficiently dry to walk on after 24 hours. Dry vacuum only during the first 7 days and remove liquid spillages immediately. The surface will gradually increase in water resistance. Any initial light water marking is easily removed by soft nylon pad in conjunction with TIMBEREX® Maintenance products and cleaners.

SIKKERHETSDATA

VOC ferdigblandet: < 275 g/l
Merknader angående sikkerhet: The product is not hazardous or dangerous to inhale. Ensure good ventilation when using the oil. All product labels provide general safety information. Material safety data sheets are available on www.timberex.com. Food products must be removed from the area during application and cure. Applicators, cloths etc impregnated with the product should be put in a bucket of water and placed outside the building to avoid the possibility of spontaneous combustion. The contents should be disposed of according to local regulations.

HOLDBARHET

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

Utstedt dato: 24/03/2025

Tilgjengelige farger & størrelse på forpakninger: Vennligst referer til den respektive produktsiden på www.rust-oleum.eu for en oversikt over tilgjengelige farger og størrelse på forpakninger.

Ansvarsfraskrivelse: Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstillende Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukerne er selv ansvarlige for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatabladet er tilgjengelig, og kan lastes ned gratis fra www.rust-oleum.eu, eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu